

JAZZ BAND®

HEARING BANDS

NRR
25
dB



HEARING PROTECTION

Jazz Band® now has a higher NRR 25 with 50% less band pressure.

The new Jazz Band has been redesigned with increased protection and comfort in mind. We increased the NRR by designing the soft tapered foam pods to correspond to the shape of the ear canal.

A more comfortable Jazz Band was achieved by decreasing the band pressure. The end result is greater user fit and comfort which can increase compliance. Workers will want to wear it all day long. The Jazz Band easily hangs around the neck when not in use with the optional breakaway cord.

FEATURES

- New, higher NRR 25.
- New, band pressure is reduced by 50%.
- Extra soft tapered foam pods gently conform to the ear canal.
- Jazz Band is the ideal choice for intermittent usage.
- Hangs easily around neck with optional breakaway cord.
- Greater comfort and fit for increased compliance and convenience.
- A cooler and lighter alternative to earmuffs.
- Jazz Band does not interfere with eyewear.
- Jazzy style increases worker acceptance.
- Includes an extra pair of pods.
- Jazz Band is independently tested to ANSI S3.19-1974.
- 100% PVC-Free.



MOLDEX
Ideas that wear well.

JAZZ BAND[®]

HEARING BANDS

PART # / DESCRIPTION	DISPLAY	CASE
6506 Jazz Band	10 Bands per Box	5 Boxes per Case
6504 Replacement Pods	5 Pairs/1 Neck Cord/Bag	50 Bags

WARNING TO USER

1. Use this laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn.
2. Failure to follow all instructions could result in hearing loss or injury.
3. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
4. Hearing bands must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
5. Overprotection can be dangerous. The wearer must be able to hear warning signals.
6. Wearers with hearing loss should exercise extreme caution.
7. It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace.
8. Use caution when working around machinery or other equipment to ensure neck cord does not become caught or entangled.
9. Failure to follow these warnings could result in serious injury or death.
10. Only use/wear under the chin.

MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 or E-mail: tech@moldex.com or visit www.moldex.com.

Keep pods away from infants and small children as they may get caught in the windpipe and create a choking hazard.



ATTENUATION DATA – UNDER-THE-CHIN

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR 25	CSA AL
Mean Attenuation (dB)	31.3	32.4	32.3	31.7	36.1	40.1	41.7	44.9	43.2		
Standard Deviation (dB)	5.4	5.4	4.5	3.9	4.0	4.1	5.0	3.8	4.4		



MOLDEX[®]
Ideas that wear well.



Printed on Recycled Paper